

THE BOLD NEW AGE



ALL-NEW ISUZU

D-MAX

Specifications:

ISUZU D-MAX 3.0 Ddi V-CROSS A/T

www.isuzu.co.za f X @ in

ISUZU

With you, for the long run

ISUZU D-MAX 3.0 Ddī V-CROSS A/T

ENGINE		
Engine Code	4JJ3	
Displacement (cc)	2 999	
No. of Cylinders	4	
Compression Ratio	16.3:1	
Bore X Stroke (mm)	95.4 X 104.9	
No. of Valves	16	
Power (kW) @ r/min	140 @ 3 600	
Torque (Nm) @ r/min	450 @ 1 600 – 2 600	
Turbocharger	Standard	
800 mm Water Depth Protection	Standard	
Pre-Air Cleaner	Standard	
ACG (90 A)	Standard	
ACG with with Intelligent Battery System (IBS)	Standard	
Intercooler	Standard	

FUEL CONSUMPTION ¹		
Combined Cycle (Litres/100 km)	7.9	
Combined CO ₂ Emissions (g/km)	208	
Fuel Type	Diesel	

TRANSMISSION		
Transmission Type	6-Speed Automatic	
Gear Ratio: 1st	3.600	
Gear Ratio: 2nd	2.090	
Gear Ratio: 3rd	1.488	
Gear Ratio: 4th	1.000	
Gear Ratio: 5th	0.687	
Gear Ratio: 6th	0.580	
Gear Ratio: Reverse	3.732	
4WD Selector	–	
Low Range Ratio	–	

FRONT DIFFERENTIAL		
Shift on the Fly up to 100 km / hour	–	
Axle Ratio: Final Drive	–	

REAR DIFFERENTIAL		
Differential Lock	Standard	
Axle Ratio: Final Drive	3.727	

CHASSIS DESIGN		
Front Wheel Suspension	High Mounting	
Rear Wheel Suspension	Leaf Spring Overslung	
Shock Absorbers	Twintube Gas Pressurised	
Suspension	High-Ride	
Skid Plate Guard Front	Standard	
Skid Plate Guard Rear	Standard	
Engine Sump Guard	Standard	
Transfer Case Guard	–	
Oil Pan Guard	Standard	

WHEELS AND TYRES		
Tyre Size	265 / 60 R 18	
Wheels Size / Type	18" X 7.5J-33 Alloy	
Spare Wheel Size / Type	18" X 7.5J-33 Alloy	
Turning Circle (m)	12.5	
Tyre-Pressure Monitoring Sensor	Standard	

DIMENSIONS		
Length (mm)	5 333	
Width (mm)	1 880	
Height (mm)	1 810	
Wheelbase (mm)	3 125	
Front / Rear Track (mm)	1 570 / 1 570	
Rear Overhang (mm)	1 318	
Ground Clearance (mm)	232	
Loadbox Length (mm)	1 495	
Loadbox Width (mm)	1 530	
Loadbox Depth (mm)	490	
Approach Angle (°)	30	
Departure Angle (°)	18	
Breakover Angle (°)	22.5	
Wading Depth (mm)	800	

MASS / CAPACITY		
Gross Axle Mass – Front (GA1) (kg)	1 450	
Gross Axle Mass – Rear (GA2) (kg)	1 910	
Gross Vehicle Mass (GVM) (kg)	3 000	
Gross Combined Mass (GCM) (kg)	6 000	
Tare Mass (kg)	1 980	
Payload (kg)	960	
Towing Capacity (kg): Unbraked Trailer ²	750	
Towing Capacity / Rating (kg): Braked Trailer ²	3 500	
Fuel Tank Capacity (Litres)	76	

LOADBOX FEATURES		
Tiedown Brackets in Loadbox for Load Restraint	4	
Rope Hooks on Loadbox Side	–	

SAFETY FEATURES		
Anti-Lock Braking System (ABS)	Standard	
Electronic Brake-Force Distribution (EBD)	Standard	
Brake-Assist System (BAS)	Standard	
Electronic Stability Control (ESC) with Traction Control	Standard	
Hill-Start Assist (HSA)	Standard	
Hill-Descent Control (HDC)	Standard	
Trailer Sway Control	Standard	
Cruise Control	Standard, Adaptive	
Brake-Override Accelerator (BOA)	Standard	
Multi-Collision Brake	Standard	
Height-Adjustable 3-Point Front Seatbelts	Standard	
Front Seat Centre Lap Belt (2-Point)	–	
Seatbelt Pre-Tensioners	Standard	
Fixed 3-Point Rear Seatbelts	Standard	
Seatbelt Reminder	Driver & Passenger and Rear Passengers	
Occupant Detection Sensor	Front and Rear Passengers	
Driver and Passenger Airbags	Standard	
Front Seat Side Airbags	Standard	
Curtain Airbags	Standard	
Knee Airbag	Driver	
Far Side Airbag	Standard	
Side-Impact Protection Bars	Standard	
Improve Side-Pole Impact	–	
Collapsible Steering Column	Standard	
Speed-Sensitive Door Lock	Standard	
ISOFIX Child-Seat Attachment	Standard with Top Tether	
Parking Distance Sensors	Front and Rear	
Rear-View Camera	Standard	
Front Camera	Standard	
Warning Triangle Kit	Standard	
Emergency Stop Signal	Standard	
Blind-Spot Monitor	Standard	
Rear Cross-Traffic Alert	Standard	
Rear Radar	Standard	
Autonomous Emergency Brake	Standard	
Forward-Collision Warning	Standard	
Pedal Misapplication Mitigation	Standard	
Manual Speed Limiter	Standard	
Lane-Departure Warning	Standard	
Lane-Keep Assist	Standard	
Lane-Departure Prevention	Standard	
Driver Monitoring	Standard	

SECURITY FEATURES		
Manual Door Locks	–	
Remote-Controlled Central Locking	–	
Remote Engine Start	Standard	
Remote Keyless Entry	–	
Passive Entry Start System (PRESS)	Standard	
Child-Proof Rear Door Locks	Standard	
Anti-Theft Alarm System	Standard	
Ultrasonic Alarm	Standard	
Transponder Immobiliser System	Standard	
Selectable Door Unlock	Standard	
Walk-Away Auto Door Lock	Standard	

INTERIOR / EXTERIOR LIGHTING		
Front Reading Lamps	Standard	
Interior Courtesy Lamps	Standard	
Illuminated Entry	Standard	
Front Fog Lamps	Standard / LED	
Daytime Running Lights (DRL)	LED	
Headlamps	LED	
Headlamp Levelling	Automatic	
Headlamps 'ON' Warning Buzzer	Standard	
Automatic On/Off Headlamp	Standard	
Automatic High Beam	Standard	
Turn Indicator Lamp on Door	–	
Rear Taillights – Combination	LED	
High-Mounted Centre Stop Lamp	Standard	
Rear Fog Lamps	Standard	
Follow-Me-Home Headlamps	Standard	

EXTERIOR FEATURES		
Front Wiper	Auto / Rain-Sensing	
Radiator Grille	Gun Metallic	
Front Bumper	High Appearance	
Rear Bumper	Body Colour	
Front Bumper Cladding	Standard Gun Metallic	
Towbar	Standard (3.5T)	
Exterior Door Handle	Dark Grey Metallic Gun Metallic, Power Adjustment and Folding, Heated, Side Indicator, Driver Side Aspherical	
Exterior Mirror	Standard	
B-Pillar Blackout	Standard	
Over Fender (Fender Flares)	Standard Gun Metallic	
Roof Rails	Standard	

Sports Bar	–
Sports Hoop	Standard Gun Metallic
Side-Steps	Standard Medium Grey
Mudflaps	Front and Rear
Tailgate Handle	Dark Grey Metallic

INTERIOR FEATURES		
Power-Assisted Steering (PAS)	Electric	
Air Conditioning	Automatic, Dual Zone	
Pollen Filter	Standard	
Inside Rear-View Mirror	Auto Diming	
Sunvisor	Driver and Passenger with Vanity Mirror Light	
Overhead Console with Map Lamps (X2) and Sunglasses Holder	Standard	
Digital Clock	Standard	
Multi-Information Display (MID)	Standard	
Dashboard Illumination Control	Standard	
Power Socket – Auxiliary 12V IP Mounted	1	
Cigarette Lighter	Standard	
Lockable Glove Box	Standard	
Utility Box on Glove Box	Standard – High Type	
Steering Column Adjustment	Tilt and Telescopic	
Steering Wheel Trim	Leather	
Steering Wheel Multi-Functional Controls	Audio, SAS, Auto Cruise and Adaptive Cruise Control	
Gear Shift Trim	Leather with Decorate	
Front Seat Configuration	Bucket Seats (x2)	
Rear Seat Configuration	60:40 Split-Cushion Bench	
Seat Trim	Partial Leather	
Seat Adjustment	8-Way Power Driver, Power Lumbar Support Driver	
Storage Pockets behind Front Seats	Standard	
Door Trim with Storage Pockets and Integrated Cupholders	Standard	
Interior Door Release Handle	Chrome	
Interior Trim Colours	Black Upper / Black Lower	
A-pillar Assist Grip – Driver and Passenger	Standard	
Roof-Mounted Assist Grips	Driver and Passengers	
Floor Trim	Carpet with Heel Pad and Tibia Pad	
Floor Tunnel Console with Integrated Cupholder	Standard	
Centre Console Storage Box with Lid	Standard with Soft Pad with Stitch	
Driver Footrest	Standard	
Rear Heater Duct	–	
Rear Ventilation Duct	Standard	
Storage Box	–	
Window Operation	Power Front and Rear with Driver One-Touch, Jam Protection and Timer	
Rear Window	Fixed with Defogger	
Fuel Flap Remote Opener	Standard	
Ventilator Grille with Shutter (Fin Shut)	Standard	

INFOTAINMENT		
Audio System	AM/FM Radio, 9" Touchscreen, Bluetooth® – Audio Streaming, Apple CarPlay® & Android Auto, Wi-Fi & Hands-Free Phone	
USB Port (Music Playback and Device Link)	Standard	
USB Charge Port	Rear	
Speakers	8	
Antenna	Standard	

OPTIONS		
17" Alloy Wheel	–	
18" Alloy Wheel and 265 / 60 R 18 Tyre (All Terrain)	–	
18" Alloy Wheel and 265 / 60 R 18 Tyre (H/T Terrain)	Available	
Differential Lock	–	
Hubcap Steel Wheel	–	
Hubcap Alloy Wheel	–	
Spare Tyre Steel	–	
Spare Tyre Alloy	–	
Sports Bar – Black	–	
Sports Bar – Chrome	–	
Rear Sliding Window	Available	
Partial Leather Seat with Manual Adjustment	–	

WARRANTY / SERVICE INTERVALS		
Warranty and Roadside Assistance	5 Years / 120 000 km	
Anti-Corrosion Warranty	5 Years / Unlimited km	
Service Plan	5 Years / 90 000 km	
Service Intervals	12 Months / 15 000 km	

1 Fuel Economy and CO₂ data as per ECE R101 / SANS 20101 regulation. Note that the actual fuel consumption will depend on many factors, including the driver's driving habits, prevailing conditions and the vehicle's equipment, condition and use.

2 Towing capacity subject to South African Road Traffic Act. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle and trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 and GA2) must not be exceeded (e.g.: if a 3.0L Diesel is towing 3,500kg, its maximum Vehicle mass is 2,500kg in order to be within GCM).